

Alerts you at the of a spark

Advanced Alerting System

Godrej Security Solutions presents Fi-Warn, an advanced fire alerting system. Godrej Fi-Warn has adjustable sensitivity, fire, heat, and smoke detection.

GFW1800

- **Multiprotocol panel:** The panel is compatible with more than one make of addressable devices
- **Redundancy:** Redundancy for all critical components like CPU, loop card and network cards thus ensuring high uptime for critical life safety applications
- **Expandability & networkability:** From 1-18 loops, and 128 such panels can be networked thus making the panel very versatile
- **World Class Listings:** EN54 listed, VdS certification for products and systems
- **Application:** Commercial buildings, industrial areas, government assets, airports, railway and metro stations



GFW200

- **Multiprotocol panel:** The panel is compatible with multiple makes of addressable devices
- **Expandability:** 1-2 loops
- **Easy installation:** Out of the box onto the wall
- **World Class Listings:** EN54 Listed, VdS certification for products and Systems
- **Applications:** Small shops, banks, offices, buildings



Godrej Security Solutions also has a range of detectors and devices, to suit all needs. From heat detection, to smoke detection, to multi-criteria detection, our devices have all your fire safety needs covered. To top it off, all our devices are loop powered, negating the need for an external power supply.

Key Features for Detector/Devices

1. Multi-criteria Detector:

- Heat and photoelectric elements are combined to give the output
- 5 modes of operation



2. Optical Smoke Detector:

- Works on the light scattering principle.



3. Fixed Temperature Heat Detector:

- Fixed temperature heat detected at 55° C



4. Indoor Manual Call Point:

- Easy access, front reset mechanism
- Front facing addressing
- IP 54 rated



5. Outdoor Manual Call Point:

- Easy access, front reset mechanism
- Front facing addressing
- IP67 rated



6. Isolating Base:

- The base is loop – powered, polarity sensitive, and sets the associated device address



7. Integrated Base Sounder:

- Available in two volume ranges: 55-76dB & 75-91dB
- Built-in isolator
- Optical R-CAP



8. Outdoor Addressable Sounder:

- Two volume settings: 92dB (A) and 100dB (A)
- Built-in isolator



9. Outdoor Sounder Visual:

- Two volume settings 92dB (A) and 100dB (A)
- Built-in isolator
- Weatherproof version available (A-SV-OD)



(A-SV-OD)

10. Input / Output Interface:

- It provides 2 inputs and 2 outputs, enabling multiple functionality
- The input cum output interface is fitted with a bi-directional short-circuit isolator



11. Output Interface:

- The output interface has 2 relay outputs
- It is fitted with a bi-directional, short circuit isolator



12. Isolator Device:

- Detects wiring short circuits



Disclaimer: In view of the Godrej policy of continuous development and improvement, the dimensions as seen on the catalog of the product may not match with the actual product. The color combinations of the products as seen on this catalog may vary, and not match the actual color of the product due to printing limitations.

Godrej & Boyce Mfg. Co. Ltd.

Plant No. 17, Pirojshanagar, Vikhroli (E), Mumbai – 400 079

Tel. No.: 022 6796 1700/1800 Fax No.: 022 6796 1509

Toll-free No.: 1800 209 99 55 | SMS 'GSS' to 53636 | secure@godrej.com | www.godrejsecure.com

(Service across 20 branches and an extensive dealership network)

ISO 9001:2008, ISO 14001:2004 & BS OHSAS 18001:2007

Follow us on:

